


HEAVY DUTY STEEL POST SHORE

POST SHORES

Heavy-Duty Post Shores are primarily used in heavy construction applications and re-shoring.

GENERAL SPECIFICATIONS

- Post OD 3" / 76.0mm
- Staff OD 2.5" / 63.5mm
- Quick Release Pin
- Striker/Dismantle Support
- Universal hole schedule on base plates
- Load capacity is based in a safety factor of 3:1.
- **Material:** Steel
- **Finish:** Hot dipped galvanized, painted finish available upon request



Part No.	Description	Extension	Weight
SHPSHD611	Post Shore, 6'-6" to 11'-6"	6'-6" to 11'-6" / 1.98 m - 3.51 m	46.3 lb / 21.00 kg
SHPSHD1018	Post Shore, 10' to 18'	10' to 18' / 3.05 m - 5.49 m	74.1 lb / 33.61 kg

HEAVY DUTY STEEL POST SHORE CAPACITIES

POST SHORES

Load capacity is based in a safety factor of 3:1.

*NOTE: Using the appropriate Post Shore Extension these load ratings are valid only when the extensions are secured to the shoring posts, using 4-1/2" grade 5 bolts. Nuts should be tightened to a minimum of 45'-lbf.

Extension	Allowable Load Capacity	
	SHPSHD611	SHPSHD1018
6'-6" / 2.01 m	7750 lb / 34.47 kN	
7' / 2.13 m	7400 lb / 32.92 kN	
7'-6" / 2.31 m	7050 lb / 31.36 kN	
8' / 2.43 m	6700 lb / 29.8 kN	
8'-6" / 2.62 m	6350 lb / 28.25 kN	
9' / 2.74 m	6000 lb / 26.69 kN	
9'-6" / 2.92 m	5650 lb / 25.13 kN	
10' / 3.04 m	5300 lb / 23.58 kN	9900 lb / 44.03 kN
10'-6" / 3.23 m	4950 lb / 22.02 kN	9500 lb / 42.26 kN
11' / 3.35 m	4600 lb / 20.46 kN	9050 lb / 40.26 kN
11'-6" / 3.53 m	4200 lb / 18.68 kN	8625 lb / 38.37 kN
12' / 3.65 m	3850 lb / 17.25 kN*	8200 lb / 36.48 kN
12'-6" / 3.84 m	3525 lb / 15.79 kN*	7775 lb / 34.58 kN
13' / 3.96 m	3150 lb / 14.11 kN*	7350 lb / 32.69 kN
13'-6" / 4.14 m	2800 lb / 12.54 kN*	6925 lb / 30.8 kN

Extension	Allowable Load Capacity
	SHPSHD1018
14' / 4.26 m	6500 lb / 28.91 kN
14'-6" / 4.45 m	6075 lb / 27.02 kN
15' / 4.57 m	5650 lb / 25.13 kN
15'-6" / 4.75 m	5225 lb / 23.24 kN
16' / 4.87 m	4800 lb / 21.35 kN
16'-6" / 5.05 m	4375 lb / 19.46 kN
17' / 5.18 m	3950 lb / 17.57 kN
17'-6" / 5.36 m	3525 lb / 15.68 kN
18' / 5.48 m	3100 lb / 13.79 kN
18'-6" / 5.64 m	2650 lb / 11.87 kN*
19' / 5.79 m	2250 lb / 10.08 kN*
19'-6" / 5.94 m	1800 lb / 8.06 kN*
20' / 6.1 m	1400 lb / 6.27 kN*